

	Part No.	HP4X100V1X
	Specifications	
	Color	Ww/Nw/Cw
	Color Temp(Kevin)	3000K/4000K/5000K/6000K
	Lumen(lm)	12000 (Clear Diffuser)
	CRI(Ra)	>80
	Wattag (w)	100
	Beam Angle	120°
	Power supply	Meanwell AC100-240/277V
	Installation	Surface mounted/Suspension
	Dimmable	1-10Vdc/PWM/resistance
	Dimension (mm)	1265*240*110
	LED Type	Samsung 5630 240pcs
	Housing	aluminum body
	Housing Color	aluminum
Optics( Cover)	Clear or milky	
Applications	IP65 rate Class I	
Price	<a href="#">Contact Us</a>	


Image

	Part No.	HP4X100V2X
	Specifications	
	Color	Ww/Nw/Cw
	Color Temp(Kevin)	3000K/4000K/5000K/6000K
	Lumen(lm)	12000 (Clear Diffuser)
	CRI(Ra)	>80
	Wattag (w)	100
	Beam Angle	120°
	Power supply	Meanwell <b>AC200-480V</b>
	Installation	Surface mounted/Suspension
	Dimmable	1-10Vdc/PWM/resistance
	Dimension (mm)	1265*240*110
	LED Type	Samsung 5630 240pcs
	Housing	aluminum body
	Housing Color	aluminum
Optics( Cover)	Clear or milky	
Applications	IP65 rate Class I	
Price	<a href="#">Contact Us</a>	



Image

	Part No.	HP4X120V1X
	Specifications	
	Color	Ww/Nw/Cw
	Color Temp(Kevin)	3000K/4000K/5000K/6000K
	Lumen(lm)	14400 (Clear Diffuser)
	CRI(Ra)	>80
	Wattag (w)	120
	Beam Angle	120°
	Power supply	Meanwell AC100-240/277V
	Installation	Surface mounted/Suspension
	Dimmable	1-10Vdc/PWM/resistance
	Dimension (mm)	1265*240*110
	LED Type	Samsung 5630 330pcs
	Housing	aluminum body
	Housing Color	aluminum
Optics( Cover)	Clear or milky	
Applications	IP65 rate Class I	
Price	<a href="#">Contact Us</a>	



Image

	Part No.	HP4X120V2X
	Specifications	
	Color	Ww/Nw/Cw
	Color Temp(Kevin)	3000K/4000K/5000K/6000K
	Lumen(lm)	14400 (Clear Diffuser)
	CRI(Ra)	>80
	Wattag (w)	120
	Beam Angle	120°
	Power supply	Meanwell <b>AC200-480V</b>
	Installation	Surface mounted/Suspension
	Dimmable	1-10Vdc/PWM/resistance
	Dimension (mm)	1265*240*110
	LED Type	Samsung 5630 330pcs
	Housing	aluminum body
	Housing Color	aluminum
Optics( Cover)	Clear or milky	
Applications	IP65 rate Class I	
Price	<a href="#">Contact Us</a>	

Image

	Part No.	HP4X150V1X
	Specifications	
	Color	Ww/Nw/Cw
	Color Temp(Kevin)	3000K/4000K/5000K/6000K
	Lumen(lm)	18000 (Clear Diffuser)
	CRI(Ra)	>80
	Wattag (w)	150
	Beam Angle	120°
	Power supply	Meanwell AC100-240/277V
	Installation	Surface mounted/Suspension
	Dimmable	1-10Vdc/PWM/resistance
	Dimension (mm)	1265*240*110
	LED Type	Samsung 5630 360pcs
	Housing	aluminum body
	Housing Color	aluminum
Optics( Cover)	Clear or milky	
Applications	IP65 rate Class I	
Price	<a href="#">Contact Us</a>	

Image

	Part No.	HP4X150V2X
	Specifications	
	Color	Ww/Nw/Cw
	Color Temp(Kevin)	3000K/4000K/5000K/6000K
	Lumen(lm)	18000 (Clear Diffuser)
	CRI(Ra)	>80
	Wattag (w)	150
	Beam Angle	120°
	Power supply	Meanwell <b>AC200-480V</b>
	Installation	Surface mounted/Suspension
	Dimmable	1-10Vdc/PWM/resistance
	Dimension (mm)	1265*240*110
	LED Type	Samsung 5630 360pcs
	Housing	aluminum body
	Housing Color	aluminum
Optics( Cover)	Clear or milky	
Applications	IP65 rate Class I	
Price	<a href="#">Contact Us</a>	

Image



**Gorgeous Lighting Co.,Ltd.**

ledlight@saving-star.com, savingledlight@gmail.com

Cell:+86 189 6518 3418 Tel: +86 592 559 4418

