

	Part No.	L02-24W-600-(O)
	Specifications	
	Color	Ww/Nw/Cw
	Color Temp(Kevin)	3000K/4000K/6000K
	Lumen(lm)	2040 (Milky Diffuser)
	CRI(Ra)	>80
	Wattag (w)	24
	Beam Angle	120°
	Power supply	AC100-240/277V
	Installation	Surface mounted
	Dimmable	No
	Dimension (mm)	685*64*69
	LED Type	EPISTAR 2835 50pcs
	Housing	high impact resistant PC
	Housing Color	Black
Optics(Cover)	Clear or milky	
Applications	IP65 rate Class I	
Price	Contact Us	


Image

	Part No.	L02-24W-1200-(O)
	Specifications	
	Color	Ww/Nw/Cw
	Color Temp(Kevin)	3000K/4000K/6000K
	Lumen(lm)	2050 (Milky Diffuser)
	CRI(Ra)	>80
	Wattag (w)	24
	Beam Angle	120°
	Power supply	AC100-240/277V
	Installation	Surface mounted
	Dimmable	No
	Dimension (mm)	1285*64*69
	LED Type	EPISTAR 2835 50pcs
	Housing	high impact resistant PC
	Housing Color	Black
Optics(Cover)	Clear or milky	
Applications	IP65 rate Class I	
Price	Contact Us	



Image

	Part No.	L02-36W-1200-(O)
	Specifications	
	Color	Ww/Nw/Cw
	Color Temp(Kevin)	3000K/4000K/6000K
	Lumen(lm)	3060 (Milky Diffuser)
	CRI(Ra)	>80
	Wattag (w)	36
	Beam Angle	120°
	Power supply	AC100-240/277V
	Installation	Surface mounted
	Dimmable	No
	Dimension (mm)	1285*64*69
	LED Type	EPISTAR 2835 70pcs
	Housing	high impact resistant PC
	Housing Color	Black
Optics(Cover)	Clear or milky	
Applications	IP65 rate Class I	
Price	Contact Us	

Image

	Part No.	L02-36W-1500-(O)
	Specifications	
	Color	Ww/Nw/Cw
	Color Temp(Kevin)	3000K/4000K/6000K
	Lumen(lm)	3100 (Milky Diffuser)
	CRI(Ra)	>80
	Wattag (w)	36
	Beam Angle	120°
	Power supply	AC100-240/277V
	Installation	Surface mounted
	Dimmable	No
	Dimension (mm)	1585*64*69
	LED Type	EPISTAR 2835 84pcs
	Housing	high impact resistant PC
	Housing Color	Black
Optics(Cover)	Clear or milky	
Applications	IP65 rate Class I	
Price	Contact Us	

Image

	Part No.	L02-50W-1500-(O)	
	Specifications		
	Color	Ww/Nw/Cw	
	Color Temp(Kevin)	3000K/4000K/6000K	
	Lumen(lm)	4250 (Milky Diffuser)	
	CRI(Ra)	>80	
	Wattag (w)	50	
	Beam Angle	120°	
	Power supply	AC100-240/277V	
	Installation	Surface mounted	
	Dimmable	No	
	Dimension (mm)	1585*64*69	
	LED Type	EPISTAR 2835 84pcs	
	Housing	high impact resistant PC	
	Housing Color	Black	
Optics(Cover)	Clear or milky		
Applications	IP65 rate Class I		
Price	Contact Us		

Image

Kindly note, the MOQ is 300pcs, the price will be 10% higher for less quantity.

Features:

- 1) Name: L02 IP65 LED Waterproof Lighting
- 2) Input Voltage:100-240/277V AC; Frenquency: 50/60Hz
- 3) IP Rating: IP65 Class: I
- 4) Housing: PC, high impact resistant,IK08,glow wire testing 850 degrees;
- 5) Diffuser: PC, high impact resistant, IK08, glow wire testing 850 degrees, Opal color, >82% transmission
- 6) LED driver: XZ brand constant current LED driver;
- 7) LED module : EPISTAR 2835, With PCB board
- 8) Cable: 0.5MM2 VDE certified
- 9) Cable gland: PG13.5 waterproof tightening gland
- 10) Fixation: stainless mounting brackets (2pcs)
- 11) Packing: inner box + brown master carton
- 12) Installation: under ceiling or wall-mounted or pendanted
- 13) Instrution paper: one A4 paper printing user instution manuel
- 14) Ambient Temperature: -20°C ~ +40°C
- 15) Three years warranty.

Below three colors of end-caps are available

